

## Calderas de Pie Sime - RMG / RS / AR / 1R / 2R / RONDO



### RMG

Caldera a gas de hierro fundido con quemador atmosférico y encendido electrónico.  
Potencia eléctrica: 16 w (excepto RMG 110 69w)

Modelo	Código	Potencia Térmica		Cap. lt	Peso kg
		Nominal kcal/H	Imput kcal/H		
<b>RMG 70</b>	<b>00.160.73</b>	60.300	67.000	27	238
<b>RMG 80</b>	<b>00.160.74</b>	67.700	75.200	30	266
<b>RMG 90</b>	<b>00.160.75</b>	77.400	86.000	33	294
<b>RMG 100</b>	<b>00.160.76</b>	84.800	94.200	36	322
<b>RMG 110</b>	<b>00.160.77</b>	92.800	103.600	37	350



### RS

Caldera a gas de hierro fundido con quemador atmosférico y encendido electrónico.  
Potencia eléctrica: 80 w

Modelo	Código	Potencia Térmica		Cap. lt	Peso kg
		Nominal kcal/H	Imput kcal/H		
<b>RS 129</b>	<b>00.169.50</b>	110.900	125.450	67,5	266
<b>RS 151</b>	<b>00.169.51</b>	129.500	146.200	77	294
<b>RS 172</b>	<b>00.169.52</b>	148.100	167.000	86,5	322
<b>RS 194</b>	<b>00.169.53</b>	166.600	187.650	96	350
<b>RS 215</b>	<b>00.169.54</b>	185.000	208.200	105,5	378
<b>RS 237</b>	<b>00.169.55</b>	203.400	228.750	115	406
<b>RS 258</b>	<b>00.169.56</b>	221.700	249.400	124,5	434
<b>RS 279</b>	<b>00.169.57</b>	240.000	269.000	134	462



### AR - RONDO - 1R - 2R

Caldera a gas de hierro fundido para quemadores de petróleo/parafina o gas soplado.  
Quemador no incluido.



Modelo	Código	Potencia Térmica		Cap. lt	Peso kg	Quem. Riello Sugerido	
		Nominal kcal/H	Imput kcal/H			Petróleo	Gas
<b>AR - 4</b>	<b>00.169.61</b>	25.300	29.400	23	122	40G5	40GS5
<b>AR - 5</b>	<b>00.169.62</b>	34.400	39.000	27	147	40G5	40GS5
<b>RONDO - 6</b>	<b>00.169.63</b>	41.400	45.600	24,8	186	40G5	40GS5
<b>RONDO - 7</b>	<b>00.169.64</b>	49.500	54.400	28,8	212	40G10	40GS10
<b>1R - 7</b>	<b>00.169.67</b>	63.600	71.500	42	293	40G10	40GS10
<b>1R - 8</b>	<b>00.169.68</b>	72.200	80.700	46,5	325	40G10	40GS10
<b>1R - 9</b>	<b>00.169.69</b>	80.200	88.900	51	357	40G10	40GS10
<b>2R - 6</b>	<b>00.169.71</b>	86.500	97.600	92	462	40G20	40GS20
<b>2R - 7</b>	<b>00.169.72</b>	106.500	119.600	107	520	40G20	40GS20
<b>2R - 8</b>	<b>00.169.73</b>	126.500	141.600	122	578	40G20	40GS20
<b>2R - 9</b>	<b>00.169.74</b>	142.000	158.300	136	636	40G20	40GS20
<b>2R - 10</b>	<b>00.169.75</b>	154.500	171.700	151	676	40G20	40GS20
<b>2R - 11</b>	<b>00.169.76</b>	170.000	188.900	165	734	40G20S	40GS20
<b>2R - 12</b>	<b>00.169.77</b>	183.500	203.900	180	792	RL28/1	RS28
<b>2R - 13</b>	<b>00.169.78</b>	198.000	220.000	194	850	RL28/1	RS28/1
<b>2R - 14</b>	<b>00.169.82</b>	214.000	237.000	209	908	RL28/1	RS28/1
<b>2R - 15</b>	<b>00.169.79</b>	229.500	255.200	223	966	RL28/1	RS28/1